

08/27/99
jc490 U.S. PTO

A

Patent
245/177

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Attorney Docket No.: 245/177
First Named Inventor: Anthony Maglica
Prior Application Information:
Examiner: M. Tung
Art Unit: 2901

BOX PATENT APPLICATION
Assistant Commissioner for Patents
Washington, D. C. 20231

FILING UNDER 37 CFR § 1.53(B)

This is a request for filing for a

☒ continuation ☐ divisional ☐ continuation-in-part (CIP)

jc675 U.S. PTO
09/385129
08/27/99

application under 37 CFR § 1.53(b) of pending prior application Serial
No. 07/410,965 filed on September 22, 1989.

Inventor: ANTHONY MAGLICA

entitled: **FLASHLIGHT**

For CONTINUATION or DIVISION APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

I. COPY OF PRIOR APPLICATION AS FILED IS ATTACHED

☒ I hereby verify that the attached papers are a true and complete copy of what is shown in my records to be the above-identified prior application, including the oath or declaration as originally filed. (37 CFR § 1.53)

CERTIFICATE OF MAILING
(37 C.F.R. §1.10)

I hereby certify that this paper (along with any referred to as being attached or enclosed) is being deposited with the United States Postal Service on the date shown below with sufficient postage as 'Express Mail Post Office To Addressee' in an envelope addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

EL360338479US
Express Mail Label No.

Rick Moreno
Name of Person Mailing Paper

August 27, 1999
Date of Deposit

Rick Moreno
Signature of Person Mailing Paper

09385129 082799

14 Page(s) of Written Description
7 Page(s) of Claims
2 Page(s) of Abstract
2 Sheet(s) of Drawings ☐ formal ☒ informal
1 Page(s) of ☐ Declaration or ☒ Declaration and Power of Attorney
☒ Revocation of Power of Attorney and Power of Attorney (2 pages)

- ☒ Pursuant to 37 § CFR 1.63(d)(1), a newly executed oath or declaration is not required.
- ☐ A newly executed oath or declaration is filed herewith
- ☐ I hereby state that the amendment referred to in the declaration filed to complete the prior application, in accordance with the requirements of 37 CFR § 1.53(b), did not introduce new matter therein.

II. AMENDMENTS

- ☒ Cancel in this application original Claims 2-4 of the prior application before calculating the filing fee. (At least one original independent claim must be retained for filing purposes.)
- ☒ A Preliminary Amendment is enclosed. (Claims added by Amendment must be numbered consecutively beginning with the number next following the highest numbered original claim in the prior application.)

III. INFORMATION DISCLOSURE STATEMENT

- ☒ An Information Disclosure Statement and PTO 1449.
- ☒ A Supplemental Information Disclosure Statement and PTO 1449.

IV. PETITION FOR SUSPENSION OF PROSECUTION FOR THE TIME TO FILE AN AMENDMENT

- ☐ Filed herewith under separate cover is a petition for suspension of prosecution under 37 CFR § 1.103, together with the fee due under 37 CFR § 1.17 (h).

V. FEE CALCULATION

BASIC FILING FEE:							\$760.00
Total Claims	1	-	20	=	0	x \$18.00	\$0.00
Independent Claims	1	-	3	=	0	x \$78.00	\$0.00
Multiple Dependent Claims	\$260	(if applicable)				<input type="checkbox"/>	\$0.00
TOTAL OF ABOVE CALCULATIONS							\$760.00
Reduction by ½ for Filing by Small Entity. Note 37 CFR §§ 1.9, 1.27, 1.28. If applicable, Verified Statement must be attached.							<input type="checkbox"/> \$0.00
Misc. Filing Fees (Recordation of Assignment)							\$0.00
TOTAL FEES SUBMITTED HERewith							\$760.00

VI. SMALL ENTITY STATUS

A Verified Statement to establish small entity under 37 CFR §§ 1.9 and 1.27:

- ☐ is attached.
- ☐ has been filed in the prior application and such status is still proper and desired. [37 CFR § 1.28(a)]

VII. DRAWINGS

[NOTE: DO NOT CHECK THIS IF PRIOR CASE IS NOT TO BE ABANDONED.]

- ☐ Transfer the drawings from the prior application to this application and, subject to Item 16 below, abandon said prior application as of the filing date accorded to this application. A duplicate copy of this request is enclosed for filing in the prior application file.
[May only be used if signed by (1) applicant, (2) assignee of record or (3) attorney or agent of record and before payment of issue fee. 37 CFR § 1.138.]
- ☐ Transfer the following sheet(s) of drawings from the prior application to this application.
- ☒ New drawings are enclosed ☐ formal ☒ informal

VIII. PRIORITY - 35 USC § 119

- ☐ Priority of application Serial No. _____ filed on _____ in Country is claimed under 35 USC § 119.
- ☐ The certified copy has been filed in prior U.S. application Serial No. _____ on _____.
- ☐ The certified copy will follow.

IX. RELATE BACK - 35 USC § 120

- ☐ Amend the Specification by inserting before the first line the sentence:
This is a continuation of co-pending application Serial No. _____ filed _____, which
will issue as U.S. Patent No. _____ on _____.
- ☒ Appropriate relation back information is included in the preliminary amendment.

X. INVENTORSHIP STATEMENT

- ☒ With respect to the prior co-pending U.S. application from which this application
claims benefit under 35 USC § 120, the inventor(s) in this application is (are):

☒ the same

☐ less than those named in the prior application and it is requested that the
following inventor(s) identified above for the prior application be deleted:

[Name(s) of inventor(s) to be deleted]

- ☐ The inventorship for all the claims in this application is:

☐ the same.

☐ not the same, and an explanation, including the ownership of the various
claims at the time the last claimed invention was made, is submitted.

XI. ASSIGNMENT

- ☐ The prior application is assigned of record to _____.
- ☒ An Assignment of the invention to Mag Instrument, Inc. is attached. The Assignment
was recorded on July 31, 1986 in prior application Serial No. 06/648,032, now U.S.
Patent No. 4,577,263

XII. FEE PAYMENT BEING MADE AT THIS TIME

- ☐ Not attached. No filing fee is submitted. [This and the surcharge required by 37 CFR
§ 1.16(e) can be paid subsequently.]

☒ Attached.

- ☒ Filing fees. 760.00
- ☐ Recording assignment. [\$40.00 37 CFR § 1.21(h)(1)] —
Petition fee for filing by other than all the inventors or
person on behalf of the inventor where inventor
refused to sign or cannot be reached.
[\$130.00; 37 CFR §§ 1.47 and 1.17(h)]
- ☐ Petition fee to Suspend Prosecution for the Time —
Necessary to File an Amendment (New Application
Filed Concurrently.)
[\$130.00; 37 CFR §§ 1.103 and 1.17(i)]
- ☐ For processing an application with a specification in a —
non-English language.
[\$130.00; 37 CFR §§ 1.52(d) and 1.17(k)]
- ☐ Processing and retention fee. —
[\$130.00; 37 CFR §§ 1.53(f) and 1.21(l)]

Total Fees Enclosed 760.00

XIII. METHOD OF PAYMENT OF FEES

- ☒ Attached is a check in the amount of \$760.00.
- ☐ Charge Lyon & Lyon's Deposit Account No. **12-2475** in the amount of _____.

XIV. AUTHORIZATION TO CHARGE ADDITIONAL FEES

The Commissioner is hereby authorized to charge the following additional fees by this paper and during the entire pendency of this application to Deposit Account No. **12-2475**:

- ☒ 37 CFR § 1.16(a) (filing fees)
- ☐ 37 CFR § 1.16(b) (presentation of extra claims)
- ☐ 37 CFR § 1.16(e) (surcharge for filing the basic filing fee and/or declaration on a date later than the filing date of the application)
- ☐ 37 CFR § 1.17 (application processing fees)
- ☐ 37 CFR § 1.18 (issue fee at or before mailing of Notice of Allowance, pursuant to 37 CFR § 1.311(b))

XV. INSTRUCTIONS AS TO OVERPAYMENT

- ☒ Credit Lyon & Lyon's Deposit Account No. **12-2475**
- ☐ Refund check

XVI. POWER OF ATTORNEY

- ☐ The power of attorney in the prior application is to _____.
- ☐ The power of attorney in the prior application is to the registered attorneys and/or agents listed below and members of or associates in the law firm of **LYON & LYON LLP**, 633 West Fifth Street, 47th Floor, Los Angeles, California 90071, Registration No. 11,611, whose members are registered to practice in the U.S. Patent and Trademark office:

Roland N. Smoot, Reg. No. 18,718
Conrad R. Solum, Jr., Reg. No. 20,467
James W. Geriak, Reg. No. 20,233
Robert M. Taylor, Jr., Reg. No. 19,848
Samuel B. Stone, Reg. No. 19,297
Douglas E. Olson, Reg. No. 22,798
Robert E. Lyon, Reg. No. 24,171
Robert C. Weiss, Reg. No. 24,939
Richard E. Lyon, Jr., Reg. No. 26,300
John D. McConaghy, Reg. No. 26,733
William C. Steffin, Reg. No. 26,811
Coe A. Bloomberg, Reg. No. 26,605
J. Donald McCarthy, Reg. No. 25,119
John M. Benassi, Reg. No. 27,483
James J. Shalek, Reg. No. 29,749
Roy L. Anderson, Reg. No. 30,240

-
- ☐ The power appears in the original papers in the prior application.
- ☒ The power does not appear in the original papers, but was filed on November 6, 1985 in prior application Serial No. 06/648,032 filed September 6, 1984, now U.S. Patent No. 4,577,263.
- ☒ An associate power has been executed and is attached.
- ☐ Address all future communications to:

LYON & LYON LLP
633 West Fifth Street, 47th Floor
Los Angeles, California 90071
(213) 489-1600
Attention: Robert C. Weiss

XVII. MAINTENANCE OF CO-PENDENCY OF PRIOR APPLICATION


- ☐ A petition, fee and response has been filed to extend the term in the pending **prior** application until _____. A copy of the petition for extension of time in the **prior** application is attached.
- ☐ A conditional petition for extension of time is being filed in the pending **prior** application. A copy of the conditional petition for extension of time in the **prior** application is attached.

XVIII. ABANDONMENT OF PRIOR APPLICATION

- ☐ Please abandon the prior application at a time while the prior application is pending or when the petition for extension of time or to revive in that application is granted and when this application is granted a filing date so as to make this application co-pending with said prior application. At the same time, please add the words "now abandoned" to the amendment of the specification set forth in Item IX above.

Respectfully submitted,

LYON & LYON LLP

By: 
David A. Randall
Reg. No. 37,217

Dated: August 27, 1999

633 West Fifth Street, Suite 4700
Los Angeles, California 90071-2066
(213) 489-1600
Enclosures

Mag Instrument, Inc.
Name of Assignee

1635 South Sacramento Avenue, Ontario, CA 91761
Address of Assignee

Title of person authorized to sign on behalf of assignee:
Anthony Maglica, President

Assignment recorded in PTO on July 31, 1986, Reel 4583, Frames 250-251

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant(s):)	Group Art Unit: 2901
)	
ANTHONY MAGLICA)	Examiner:
)	
Serial No.: To Be Assigned)	
)	
Filed: Herewith)	
)	
For: FLASHLIGHT)	

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

Please amend the above-identified application as follows:

IN THE SPECIFICATION

Please delete the title.

Please cancel the entire specification as filed and substitute therefore the following text.

--This is a continuation of copending application Serial No. 07/410,965 filed September 22, 1989; which is a division of Application Serial No. 07/356,361 filed May 23, 1989, now U.S. Patent No. 4,942,505 issued July 17, 1990; which is a continuation of Application Serial No. 07/222,378 filed July 19, 1988, now U.S. Patent No. 4,899,265 issued February 6, 1990; which is a continuation of Application Serial No. 07/034,918 filed April 6, 1987, now abandoned; which is a continuation of Application Serial No. 06/828,729 filed February 11, 1986, now U.S. Patent No. 4,658,336 issued April 14, 1987; which is a continuation of Application No. 06/648,032 filed September 6, 1984, now U.S. Patent No. 4,577,263 issued March 18, 1996.

Be it known that I, ANTHONY MAGLICA, of Ontario, California, have invented a new,
original, and ornamental design for a

FLASHLIGHT

as shown in the accompanying drawings wherein:

A description of the drawings is as follows:

Figure 1 is a front perspective view of a miniature flashlight showing my new design;

Figure 2 is a side elevational view thereof, the other side being a mirror image;

Figure 3 is a bottom plan view thereof; and

Figure 4 is a front elevational view thereof.

The rear elevational view forms no part of the claimed invention.--

IN THE DRAWINGS

Please cancel the two sheets of informal drawings filed and substitute the one sheet of
drawings submitted herewith.

IN THE CLAIMS

Please cancel original claim 1.

Please enter the following new claim:

--I claim:

5. The ornamental design for a flashlight, as shown and described.--

IN THE ABSTRACT

Please cancel the Abstract.

REMARKS

Consideration of the above design application and the new design claim is respectfully requested.

As set forth in the amended Specification, first paragraph, this is a continuation of copending application Serial No. 07/410,965 filed September 22, 1989; which is a division of Application Serial No. 07/356,361 filed May 23, 1989, now U.S. Patent No. 4,942,505 issued July 17, 1990; which is a continuation of Application Serial No. 07/222,378 filed July 19, 1988, now U.S. Patent No. 4,899,265 issued February 6, 1990; which is a continuation of Application Serial No. 07/034,918 filed April 6, 1987, now abandoned; which is a continuation of Application Serial No. 06/828,729 filed February 11, 1986, now U.S. Patent No. 4,658,336 issued April 14, 1987; which is a continuation of Application No. 06/648,032 filed September 6, 1984, now U.S. Patent No. 4,577,263 issued March 18, 1996.

The foregoing requested amendments to the specification, drawings, abstract and claims of the parent utility application are editorial in nature and have been made to conform the disclosure of the parent application to the form applicable to a design patent application.

The drawings supplied herewith are perspective, elevational, front and bottom views of the flashlight design shown and described in application Serial No. 06/648,032 filed September 4, 1984, now U.S. Patent No. 4,577,263. It is noted that Figures 1 through 4 submitted herewith show various views of all aspects of the claimed design of the flashlight shown in Figures 1, 2, 3 and 8 of original parent application Serial No. 06/648,032.

Applicant relies on its prior U.S. applications for the benefit of priority under 35 U.S.C. § 120 and notes that priority for this design application is based on the previous series of utility applications as set forth above. This procedure has been approved by the U.S. Court of Appeals for the Federal Circuit. Under Racing Strollers, Inc. v. Tri Industries, Inc., Slip Opinion (Fed. Cir. 1989), the Federal circuit overruled In re Campbell, 41 CCPA 896, 212 F.2d 606, 101 USPQ 406 (1954) and observed that there is no statutory prohibition against claiming priority under 35 U.S.C. § 120 for a design patent application based on a disclosure in a utility patent application if the statutory conditions are met.

Here, Applicant submits that the design of the present application is fully set forth, as required by 35 U.S.C. § 112, first paragraph, in the parent and prior applications. Specifically, the flashlight design of the present application is the one with the appearance as described and shown in Figures 1, 2, 3 and 8 of each of the preceding parent applications back to and including application Serial No. 06/648,032.

The Information Disclosure Statements submitted in prior parent Application Serial No. 07/410,965 are included herewith for the Examiner's consideration.

It is submitted that the claim for the ornamental design shown herein is allowable and
such early action is respectfully requested.

Respectfully submitted,

LYON & LYON LLP

Dated: August 27, 1999

By



David A. Randall
Registration No. 37,217
Attorneys for Applicant

LYON & LYON LLP
633 West Fifth Street, Suite 4700
Los Angeles, California 90071-2066
Tel. No. (213) 489-1600

1.

PD-7337

MINIATURE FLASHLIGHTBACKGROUND OF THE INVENTION1. Field of the Invention.

5 The present invention relates primarily to flashlights, and in particular, to a miniature hand-held flashlight.

2. Discussion of the Prior Art.

Flashlights of varying sizes and shapes are well-known in the art. In particular, certain of such known
10 flashlights utilize two or more dry cell batteries, carried in series in a cylindrical tube serving as a handle for the flashlight, as their source of electrical energy. Typically, an electrical circuit is established from one electrode of the battery through a
15 conductor to a switch, then through a conductor to one electrode of the lamp bulb. After passing through the filament of the lamp bulb, the electrical circuit emerges through a second electrode of the lamp bulb in electrical contact with a conductor, which in turn is
20 in electrical contact with the flashlight housing. The flashlight housing provides an electrical conduction path to an electrical conductor, generally a spring element, in contact with the other electrode of the battery. Actuation of the switch to complete the
25 electrical circuit enables electrical current to pass through the filament, thereby generating light which is typically focused by a reflector to form a beam of light.

The production of light from such flashlights has
30 often been degraded by the quality of the reflector utilized and the optical characteristics of any lens interposed in the beam path. Moreover, intense light beams have often required the incorporation of as many as seven dry cell batteries in series, thus resulting
35 in a flashlight having significant size and weight.

Efforts at improving such flashlights have primarily addressed the quality of the optical

00385129-082799

characteristics. The production of more highly reflective, well-defined reflectors, which may be incorporated within such flashlights, have been found to provide a more well-defined focus thereby enhancing the quality of the light beam produced. Additionally, several advances have been achieved in the light admitting characteristics of flashlight lamp bulbs.

Since there exists a wide variety of uses for hand-held flashlights, the development of the flashlight having a variable focus, which produces a beam of light having a variable dispersion, has been accomplished. However, such advances have heretofore been directed at "full-sized" flashlights.

00385129-082799

SUMMARY OF THE INVENTION

It is a primary object of the present invention to provide a miniature hand-held flashlight having improved optical characteristics.

5 It is another object of the present invention to provide a miniature hand-held flashlight which is capable of producing a beam of light having a variable dispersion.

10 It is a further object of the present invention to provide a miniature hand-held flashlight which is capable of supporting itself vertically on a horizon surface to serve as an "ambient" unfocused light source.

15 It is another object of the present invention to provide a miniature hand-held flashlight wherein relative motions of components that produce the variation and the dispersion of the light beam provide an electrical switch function to open and complete the electrical circuit of the flashlight.

20 These and other objects of the present invention, which may become obvious to those skilled in the art through the hereinafter detailed description of the invention are achieved by a miniature flashlight comprising: a cylindrical tube containing at least two
25 miniature dry cell batteries disposed in a series arrangement, a lamp bulb holder assembly including electrical conductors for making electrical contact between terminals of a miniature lamp held therein and the cylindrical tube and an electrode of the battery,
30 respectively, retained in one end of the cylindrical tube adjacent the batteries, a tail cap and spring member enclosing the other end of the cylindrical tube and providing an electrical contact to the other electrode of the batteries, and a head assembly
35 including a reflector, a lens, and a face cap, which head assembly is rotatably mounted to the cylindrical tube such that the lamp bulb extends through a hole in

0355129 082709 662280 6215860

the center of the reflector within the lens. In the principle embodiment of the present invention, the batteries are of the size commonly referred to as "pen light" batteries.

5 The head assembly engages threads formed on the exterior of the cylindrical tube such that rotation of a head assembly about the axis of the cylindrical tube will change the relative displacement between the lens and the lamp bulb. When the head assembly is fully
10 rotated onto the cylindrical tube, the reflector pushes against the forward end of the lamp holder assembly causing it to shift rearward within the cylindrical tube against the urging of the spring contact at the tail cap. In this position, the electrical conductor
15 within the lamp holder assembly which completes the electrical circuit from the lamp bulb to the cylindrical tube is not in contact with the tube. Upon rotation of the head assembly in a direction causing the head assembly to move forward with respect
20 to the cylindrical tube, pressure on the forward surface of the lamp holder assembly from the reflector is relaxed enabling the spring contact in the tail cap to urge the batteries and the lamp holder assembly in a forward direction, which brings the electrical
25 conductor into contact with the cylindrical tube, thereby completing the electrical circuit and causing the lamp bulb to illuminate. At this point, the lamp holder assembly engages a stop which prevents further forward motion of the lamp holder assembly with respect
30 to the cylindrical tube. Continued rotation of the head assembly in a direction causing the head assembly to move forward relative to the cylindrical tube causes the reflector to move forward relative to the lamp bulb, thereby changing the focus of the reflector with
35 respect to the lamp bulb, which results in varying the dispersion of the light beam admitted through the lens.

00385139-002790

By rotating the head assembly until it disengages from the cylindrical tube, the head assembly may be placed, lens down, on a substantially horizontal surface and the tail cap and cylindrical tube may be vertically inserted therein to provide a miniature "table lamp."

09385129-082709
667280-62158800

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a perspective view of a miniature flashlight in accordance with the present invention:

5 Fig. 2 is a partially foreshortened cross-sectional view of the miniature flashlight of Fig. 1 as taken through the plane indicated by 2-2;

10 Fig. 3 is a partial cross-sectional view of a forward end of the miniature flashlight, illustrating, in ghost image, a translation of the forward end of the flashlight;

Fig. 4 is a partial cross-sectional view of a lamp bulb holder assembly used in accordance with the present invention, taken along the plane indicated by 4-4 of Fig. 3;

15 Fig. 5 is an exploded perspective view illustrating the assembly of the lamp bulb holder assembly with respect to a barrel of the miniature flashlight;

20 Fig. 6 is an isolated partial perspective view illustrating the electro mechanical interface between electrical terminals of the lamp bulb and electrical conductors within the lamp bulb holder;

25 Fig. 7 presents a perspective view of a rearward surface of the lamp bulb holder of Fig. 5, illustrating a battery electrode contact terminal; and

Fig. 8 illustrates an alternate utilization of the miniature flashlight in accordance with the present invention.

0035129 082709
662280 625860

DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

Referring first to Fig. 1, a miniature flashlight in accordance with the present invention is illustrated in perspective generally at 20. The miniature flashlight 20 is comprised of a generally right circular cylinder, or barrel 21, enclosed at a first end by a tail cap 22 and having a head assembly 23 enclosing a second end thereof. The head assembly comprises a head 24 to which is affixed a face cap 25 which retains a lens 26. The head assembly 23 has a diameter greater than that of the barrel 21 and is adapted to pass externally over the exterior of the barrel 21. The barrel 21 may provide a machined handle surface 27 along its axial extent. The tail cap 22 may be configured to include provision for attaching a handling lanyard through a hole 28 in a tab 29 formed therein.

Referring next to Fig. 2, the barrel 21 is seen to have an extent sufficient to enclose at least two miniature dry cell batteries 31 disposed in a series arrangement. The tail cap 22 has a region of external threading 32 which engages matching threads formed on the interior surface of the barrel 21. A sealing element 33, typically in the form of an O-ring, is provided at the interface between the tail cap 22 and the barrel 21 to provide a watertight seal. A spring member 34 is disposed within the barrel 21 so as to make electrical contact with the tail cap 22 and a case electrode 35 of an adjacent battery 31. The spring member 34 also urges the batteries 31 in a direction indicated by an arrow 36. A center electrode 37 of the rearmost battery 31 is in contact with the case electrode of the forward battery 31. The center electrode 38 of the forward battery is urged into contact with a first conductor 39 mounted within a lower insulator receptacle 41. The lower insulator receptacle 41 also has affixed therein a side contact

03385129-082799

00385129-082790

conductor 42. Both the center conductor 39 and the side contact conductor 42 pass through holes formed in the lower insulator receptacle in an axial direction, and both are adapted to frictionally receive and retain the terminal electrodes 43 and 44 of a miniature bi-pin lamp bulb 45. Absent further assembly, the lower insulator receptacle is urged in the direction indicated by the arrow 36, by the action of the spring 34, to move until it comes into contact with a lip 46 formed on the end of the barrel 21. At that point electrical contact is made between the side contact conductor 42 and the lip 46 of the barrel 21.

An upper insulator receptacle 47 is disposed external to the end of the barrel 21 whereat the lower insulator receptacle 41 is installed. The upper insulator receptacle 47 has extensions that are configured to mate with the lower insulator receptacle 41 to maintain an appropriate spacing between opposing surfaces of the upper insulator receptacle 47 and the lower insulator receptacle 41. The lamp electrodes 43 and 44 of the lamp bulb 45 pass through the upper insulator receptacle 47 and into electrical contact with the center conductor 39 and the side contact conductor 42, respectively, while the casing of the lamp bulb 45 rests against an outer surface of the upper insulator receptacle 47.

The head assembly 23 is installed external to the barrel 21 by engaging threads 48 formed on an interior surface of the head 24 engaging with matching threads formed on the exterior surface of the barrel 21. A sealing O-ring 49 is installed around the circumference of the barrel 21 adjacent the threads to provide a water-tight seal between the head assembly 23 and the barrel 21. A substantially parabolic reflector 51 is configured to be disposed within the outermost end of the head 24, whereat it is rigidly held in place by the lens 26 which is in turn retained by the face cap 25

which is threadably engaged with threads 52 formed on the forward portion of the outer diameter of the head 24. An O-ring 53 may be incorporated at the interface between the face cap 25 and the head 24 to provide a water-tight seal.

When the head 24 is fully screwed onto the barrel 21 by means of the threads 48, the central portion of the reflector 51 surrounding a hole formed therein for passage of the lamp bulb 45, is forced against the outermost surface of the upper insulator receptacle 47, urging it in a direction counter to that indicated by the arrow 36. The upper insulator receptacle 47 then pushes the lower insulator receptacle 41 in the same direction, thereby providing a space between the forwardmost surface of the lower insulator receptacle 41 and the lip 46 on the forward end of the barrel 21. The side contact conductor 42 is thus separated from contact with the lip 46 on the barrel 21 as is shown in Fig. 2.

Referring next to Fig. 3, appropriate rotation of the head 24 about the axis of the barrel 21 causes the head assembly 23 to move in the direction indicated by the arrow 36 through the engagement of the threads 48. Upon reaching the relative positions indicated in Fig. 3 by the solid lines, the head assembly 23 has progressed a sufficient distance in the direction of the arrow 36 such that the reflector 51 has also moved a like distance, enabling the upper insulator receptacle 47 and the lower insulator receptacle 41 to be moved, by the urging of the spring 34 (Fig. 2) translating the batteries 31 in the direction of the arrow 36, to the illustrated position. In this position, the side contact conductor 42 has been brought into contact with the lip 46 on the forward end of the barrel 21, which closes the electrical circuit.

Further rotation of the head assembly 23 so as to cause further translation of the head assembly 23 in

00385120 082709
662280-6215860

the direction indicated by the arrow 36 will result in the head assembly 23 reaching a position indicated by the ghost image of Fig. 3, placing the face cap at the position 25' and the lens at the position indicated by 26', which in turn carries the reflector 51 to a position 51'. During this operation, the upper insulator receptacle 47 remains in a fixed position relative to the barrel 21. Thus the lamp bulb 45 also remains in a fixed position. The shifting of the reflector 51 relative to the lamp bulb 45 during this additional rotation of the head assembly 23 produces a relative shift in the position of the filament of the lamp bulb 45 with respect to a focus of the parabola of the reflector 51, thereby varying the dispersion of the light beam emanating from the lamp bulb 45 through the lens 26.

Referring next to Fig. 4, a partial cross-sectional view illustrates the interface between the lower insulator receptacle 41 and the upper insulator receptacle 47. The lower insulator receptacle 41 has a pair of parallel slots 54 formed therethrough which are enlarged in their center portion to receive the center conductor 39 and the side contact conductor 42, respectively. A pair of arcuate recesses 55 are formed in the lower insulator receptacle 41 and receive matching arcuate extensions of the upper insulator receptacle 47. The lower insulator receptacle 41 is movably contained within the inner diameter of the barrel 21 which is in turn, at the location of the illustrated cross-section, enclosed within the head 24.

Referring next to Figs. 5 through 7, a preferred procedure for the assembly of the lower insulator receptacle 41, the center conductor 39, the side contact conductor 42, the upper insulator receptacle 47 and the miniature lamp bulb 45 may be described. Placing the lower insulator receptacle 41 in a position such that the arcuate recesses 55 are directionally

00385129 082769

oriented towards the forward end of the barrel 21 and the lip 46, the center conductor 39 is inserted through one of the slots 54 such that a substantially circular end section 56 extends outwardly from the rear surface of the lower insulator receptacle 41. The circular end section 56 is then bent, as shown in Fig. 7, to be parallel with the rearmost surface of the lower insulator receptacle 41 in a position centered to match the center electrode of the forwardmost one of the batteries 31 of Fig. 2. The side contact conductor 42 is then inserted into the other slot 54 such that a radial projection 57 extends outwardly from the axial center of the lower insulator receptacle 41. It is to be noted that the radial projection 57 aligns with a web 58 between the two arcuate recesses 55.

The lower insulator receptacle 41, with its assembled conductors, is then inserted in the rearward end of the barrel 21 and is slidably translated to a forward position immediately adjacent the lip 46. The lamp electrodes 43 and 44 are then passed through a pair of holes 59 formed through the forward surface of the upper insulator receptacle 47 so that they project outwardly from the rear surface thereof as illustrated in Fig. 6. The upper insulator receptacle 47, containing the lamp bulb 45, is then translated such that the lamp electrodes 43 and 44 align with receiving portions of the side contact conductor 42 and the center conductor 39, respectively. A pair of notches 61, formed in the upper insulator receptacle 47, are thus aligned with the webs 58 of the lower insulator receptacle 41. The upper insulator receptacle 47 is then inserted into the arcuate recesses 55 in the lower insulator receptacle 41 through the forward end of the barrel 21.

Referring again to Figs. 2 and 3, the electrical circuit of the miniature flashlight in accordance with the present invention will now be described.

0085129-082790

Electrical energy is conducted from the rearmost battery 31 through its center contact 37 which is in contact with the case electrode of the forward battery 31. Electrical energy is then conducted from the forward battery 31 through its center electrode 38 to the center contact 39 which is coupled to the lamp electrode 44. After passing through the lamp bulb 45, the electrical energy emerges through the lamp electrode 43 which is coupled to the side contact conductor 42. When the head assembly 23 has been rotated about the threads 48 to the position illustrated in Fig. 2, the side contact conductor 42 does not contact the lip 46 of the barrel 21, thereby resulting in an open electrical circuit. However, when the head assembly 23 has been rotated about the threads 48 to the position illustrated by the solid lines of Fig. 3, the side contact conductor 42 is pressed against the lip 46 by the lower insulator receptacle 41 being urged in the direction of the arrow 36 by the spring 34 of Fig. 2. In this configuration, electrical energy may then flow from the side contact conductor 42 into the lip 46, through the barrel 21 and into the tail cap 22 of Fig. 2. The spring 34 electrically couples the tail cap 22 to the case electrode 35 of the rearmost battery 31. By rotating the head assembly 23 about the threads 48 such that the head assembly 23 moves in a direction counter to that indicated by the arrow 36, the head assembly 23 may be restored to the position illustrated in Fig. 2, thereby opening the electrical circuit and turning off the flashlight.

Referring next to Fig. 8, an additional utilization of the miniature flashlight 20 in accordance with the present invention is illustrated. By rotating the head assembly 23 about the threads 48 in a direction causing the head assembly 23 to translate relative to the barrel 21 in the direction of the arrow 36 of Fig. 3, the electrical circuit will be

00385129-082700

closed as previously described, and the lamp bulb 45 will be illuminated. Continued rotation of the head assembly 23 in that direction enables the head assembly 23 to be completely removed from the forward end of the miniature flashlight 20. By placing the head assembly 23 upon a substantially horizontal surface (not illustrated) such that the face cap 25 rests on the surface, the tail cap 22 of the miniature flashlight 20 may be inserted into the head 24 to hold the barrel 21 in a substantially vertical alignment. Since the reflector 51 (Fig. 2) is located within the head assembly 23, the lamp bulb 45 will emit a substantially spherical illumination, thereby providing a "ambient" light level.

In a preferred embodiment, the barrel 21, the tail cap 22, the head 24, and the face cap 25, forming all of the exterior metal surfaces of the miniature flashlight 20 are manufactured from aircraft quality, heat-treated aluminum, which is anodized for corrosion resistance. The sealing O-rings 33, 49, and 53 provide atmospheric sealing of the interior of the miniature flashlight 20 to a depth of 200 feet. All interior electrical contact surfaces are appropriately machined to provide efficient electrical conduction. The reflector 51 is a computer generated parabola which is vacuum aluminum metallized to ensure high precision optics. The threads 48 between the head 24 and the barrel 31 are machined such that revolution of the head assembly 23 through less than 1/4 turn will close the electrical circuit, turning the flashlight on, and an additional 1/4 turn will adjust the light beam from a "spot" to a "soft flood". A spare lamp bulb 62 may be provided in a cavity machined in the tail cap 22.

While I have described a preferred embodiment of the herein invention, numerous modifications, alterations, alternate embodiments, and alternate materials may be contemplated by those skilled in the

00385120 082709

14.

PD-7337

art and may be utilized in accomplishing the present invention. It is envisioned that all such alternate embodiments are considered to be within the scope of the present invention as defined by the appended claims.

5

09385129.082799

I Claim:

1. A miniature flashlight comprising:
means for retaining a plurality of miniature dry
cell batteries in series electrical contact;
5 a miniature bi-pin lamp bulb;
means for holding the miniature bi-pin lamp bulb,
said means being movably retained by the means for
retaining a plurality of dry cell batteries;
a substantially parabolic reflector;
10 a substantially planar lens;
means for retaining the reflector and the lens in
a mutually fixed relationship, said means for retaining
the reflector and the lens being adapted to be
controllably translatable along the means for retaining
15 a plurality of dry cell batteries such that the
relative positional relationship between the reflector
and the lamp bulb may be varied, thereby varying a
reflection dispersion of a light beam emanating through
the lens from said miniature bi-pin lamp bulb;
20 means for electrically coupling a first electrode
of the series arranged dry cell batteries to a first
pin of the bi-pin lamp bulb; and
means for electrically coupling a second pin of
the bi-pin lamp bulb to a second electrode of the
25 series arranged dry cell batteries;
Wherein relative motion of the means for retaining
the reflector and the lens in a direction toward the
means for retaining a plurality of miniature dry cell
batteries will cause the reflector to contact the means
30 for holding the miniature bi-pin lamp bulb and further
relative motion in the same direction will move the
means for holding the miniature bi-pin lamp bulb to
open an electrical contact at the means for
electrically coupling the second pin of the bi-pin lamp
35 bulb to the second electrode of the batteries.

0035120 082799

2. A miniature flashlight, comprising:

5 a barrel containing a pair of miniature dry cell batteries in series electrical contact, said barrel having a first end and a second end, and having a radially inwardly directed annular ring formed at the second end;

10 a tail cap, including a spring member, threadably engaging with the barrel at the first end thereof, the spring member urging the dry cell batteries toward the second end of the barrel;

15 a head assembly, including a light transmitting lens and a beam forming reflector, threadably engaging a radially exterior surface of the barrel at the second end of the barrel, said reflector having a central hole formed therein adapted to enable the passage of a miniature lamp bulb there-through;

a first insulated receptacle, disposed within the barrel between the batteries and the lip formed at the second end of the barrel;

20 a center conductor member passing through the first insulated receptacle in an axial direction so as to be in electrical contact with a center electrode of the proximate battery;

25 a side conductor member mounted in the first insulated receptacle in a spaced apart relationship with the center conductor member, the side conductor member having a radially outwardly extending arm disposed between the lip formed on the second end of the barrel and a surface of the first insulated receptacle, said outwardly extending arm being spaced
30 apart from an inner diameter of the barrel;

35 a second insulated receptacle disposed external to the second end of the barrel, mechanically engaging the first insulated receptacle, said second insulated receptacle being disposed within the head assembly but not mechanically coupled thereto; and

09385129.082790

40 a miniature bi-pin lamp bulb mounted to the second insulated receptacle such that the pins thereof pass through the second insulated receptacle and are electrically coupled to the center conductor member and the side conductor member, respectively;

45 said threadable engagement of the head assembly to the barrel providing that the head assembly may translate axially with respect to the barrel to vary the position of the reflector with respect to the miniature lamp bulb, thereby providing a change in focus of a light beam emanating from the lamp bulb; and

50 whereby further translation of the head assembly along the barrel toward the tail cap will first cause the reflector to contact the second insulated receptacle and then move the second insulated receptacle, the first insulated receptacle, and the batteries against the urging of the spring member so as to separate the radially outwardly extending arm of the
55 side conductor member from the lip formed on the second end of the barrel, thereby interrupting the electrical circuit of the miniature flashlight.

09385129-082799

5

10

15

20

25

30

35

REPORT OF THE

40 a second insulated receptacle disposed external to the second end of the barrel so as to matingly engage the first insulated receptacle;

a bi-pin lamp bulb, held by the second insulated receptacle such that its two pins pass therethrough and into contact with the center contact conductor and side contact conductor, respectively;

45 a head member, configured generally as a right circular cylinder open at both ends, threadably engaging the exterior of the second end of the barrel;

50 a reflector member, having a substantially parabolic shape, disposed within the head member, the reflector member having a hole formed therein substantially at its apex through which the bi-pin lamp bulb may pass;

55 a substantially circular transparent planar lens element, the lens element retaining the reflector member within the head member; and

60 a face cap, configured as a substantially annular ring, threadably engaging with the head member, the face cap being adapted to rigidly retain the lens element and the reflector member between the face cap and the head member;

65 whereby full threadable engagement of the head member onto the barrel causes the apex region of the reflector member to come into contact with and translate the second insulated receptacle, together with the first insulated receptacle and the dry cell batteries within the barrel against the urging of the spring member, which translation displaces the radially outwardly extending arm of the side contact conductor from physical contact with the lip at the second end of the barrel, thereby opening an electrical circuit of the miniature flashlight.

70

09385129 082799

4. In a miniature flashlight providing for a continuous variation in the dispersion of a lightbeam emanating therefrom through a relative axial motion between a head assembly, containing a reflector, and a barrel assembly, containing a plurality of miniature dry cell batteries and supporting a miniature lamp bulb, the improvement comprising:

..a first insulated receptacle, disposed within the barrel between the batteries and the lamp bulb, the first insulated receptacle being removably retained within the barrel;

a center conductor element passing through the first insulated receptacle in an axial direction so as to be in electrical contact with an electrode of the proximate battery;

a side conductor member mounted in the first insulated receptacle in a spaced apart relationship with the center conductor member, the side conductor member having a radially outwardly extending arm disposed between a surface of the first insulated receptacle and a lip formed on the end of the barrel retaining the first insulated receptacle, said outwardly extending arm being spaced apart from an inner diameter of the barrel; and

a second insulated receptacle disposed external to the end of the barrel, mechanically engaging the first insulated receptacle, said second insulator receptacle being exposed within the head assembly but not mechanically coupled thereto;

whereby translation of the head assembly along the barrel in a direction engaging the head assembly with the barrel will first cause the reflector within the head assembly to contact the second insulated receptacle and then move the second insulated receptacle and the first insulated receptacle in that direction so as to separate the radially outwardly extending arm of the side conductor member from the lip

0085120 082799

on the end of the barrel, thereby interrupting the
electrical circuit of the miniature flashlight; and
40 whereby translation of the head assembly along the
barrel in a direction tending to disengage the head
assembly from the barrel will first allow the first
insulated receptacle and the second insulated
45 receptacle to follow the motion of the reflector until
the radially outwardly extending arm of the side
conductor member contacts the lip formed on the end of
the barrel, thereby closing the electrical circuit of
the miniature flashlight.

00355120 082709 662280 6215560

ABSTRACT OF THE DISCLOSURE

5 A miniature flashlight as disclosed to comprise a barrel, a tail cap, a head assembly, and means for holding a miniature lamp bulb and for providing interruptible electrical coupling to dry cell batteries retained within the barrel. The means for holding lamp bulb comprises an insulated receptacle disposed external to the end of the barrel to which the head assembly is engaged, a second insulated receptacle
10 disposed within the barrel and matingly engaging with the first insulated receptacle so as to enable the first and second insulated receptacles to translate axially through a distance limited by a flange formed on the first insulated receptacle and an annular lip formed inwardly at the end of the barrel, and a pair of
15 conductor members mounted in the second insulated receptacle such that one of the conductors serves to couple the center electrode of a dry cell battery to a first pin of the lamp bulb and the other conductor member serves to electrically couple the second pin of
20 the lamp bulb to the lip formed on the barrel. A spring is disposed between the tail cap and the batteries within the barrel to urge the batteries into contact with the center conductor on the second insulated receptacle, thereby urging the second and the
25 first insulated receptacles in the same direction until the second insulated receptacle contacts the lip on the end of the barrel whereat the second conductor member is in contact with the lip. The electrical circuit is thus closed by use of the barrel, the tail cap, and the
30 spring to couple the second pin of the lamp to the case terminal of the battery. By threadably engaging the head assembly onto the barrel in a direction causing the head assembly to translate along the barrel towards the tail cap, the reflector moves with respect to the
35 lamp bulb to cause a variation in dispersion of the reflected light beam emanating from the lamp bulb.

00385120-082799


- Further rotation of the head assembly in the same direction causes the reflector to come into contact with the first insulated receptacle, translating the first insulated receptacle, the second insulated
- 5 receptacle, and the batteries counter to the urging of the spring, until the flange on the first insulated receptacle abuts the end of the barrel, whereat the side conductor is no longer in contact with the lip of the barrel, thereby opening the electrical circuit.
- 10 The head assembly may be totally removed from the barrel and utilized as a base into which the tail cap and the barrel may be inserted to stand the miniature flashlight, in its "on" condition, for use as a miniature table lamp providing substantially uniformly
- 15 distributed light.

0035123 082749 667280 6215860

00385429.082799

PD 7337

SHEET 1 OF 2




MAG INSTRUMENT

7-23-B4

PD 7337

SHEET 2 OF 2

00385129 082799



MAG INSTRUMENT

7-83-84 °

DECLARATION
and POWER OF ATTORNEY☒ ORIGINAL
☐ CONTINUATION
☐ DIVISIONAL

As a below named inventor, I declare that the information given herein is true, that I believe that I am the original, first and sole inventor if only one name is listed at 1 below, or a joint inventor if plural inventors are named below at 1-4, of the invention entitled:

MINIATURE FLASHLIGHT

Which is described and claimed in:

☒ the attached specification or ☐ the specification in application Serial No. _____ filed _____ ☐ as amended on _____
(For declaration not accompanying application) (If applicable)

that my residence, post office address and citizenship are as stated below next to my name.

I acknowledge my duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, § 1.56 (a)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above

I hereby claim foreign priority benefits under Title 35, United States Code, § 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed

PRIOR FOREIGN APPLICATION(S)

COUNTRY	APPLICATION NUMBER	DATE OF FILING Month Day Year	PRIORITY CLAIMED UNDER 35 U.S.C. 119
			YES _____ NO _____
			YES _____ NO _____

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, § 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Serial No.) (Filing Date) (Status)

(Application Serial No.) (Filing Date) (Status)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or Agents(s) to prosecute this application and transact all business in the Patent and Trade Mark Office connected therewith.
W. ROBERT SPENSLEY, Reg. No. 17,433; MARTIN R. HORN, Reg. No. 18,189; STUART LUBITZ, Reg. No. 20,680; HOWARD A. SILBER, Reg. No. 23,036; RICHARD H. ZAITLEN, Reg. No. 27,248; JAMES E. HAWES, Reg. No. 19,680; WAYNE WILLENBERG, Reg. No. 28,488; PHILIP M. HINDERSTEIN, Reg. No. 24,123; PAUL L. GARDNER, Reg. No. 22,372; SAUL EPSTEIN, Reg. No. 25,448; DAVID L. FEHRMAN, Reg. No. 28,600; JOHN LAND, Reg. No. 29,554; WILLIAM C. SCHUBERT, Reg. No. 30,102; WILLIAM K. KONRAD, Reg. No. 28,868; VINCENT J. BELUSKO, Reg. No. 30,820; HIDEO KODA, Reg. No. 27,729; and IRVIN A. LAVINE, Reg. No. 16,838, ROBERT K. WALLOR, Reg. No. 26,595

Send correspondence to:

SPENSLEY HORN JUBAS & LUBITZ
1880 Century Park East, Suite 500
Los Angeles, California 90067

DIRECT TELEPHONE CALLS TO:

(Name and telephone number)
ROBERT K. WALLOR
(213) 553-5050

(Please Print)

1	Name of Inventor	LAST NAME MAGLICA	FIRST NAME ANTHONY	MIDDLE NAME NMI	Residence: CITY Ontario	STATE or COUNTRY California
	Post Office Address 219 Armsluy Square, Ontario, California 91762					CITIZENSHIP U.S.A.
2	Name of Inventor	LAST NAME	FIRST NAME	MIDDLE NAME	Residence: CITY	STATE or COUNTRY
	Post Office Address					CITIZENSHIP
3	Name of Inventor	LAST NAME	FIRST NAME	MIDDLE NAME	Residence: CITY	STATE or COUNTRY
	Post Office Address					CITIZENSHIP
4	Name of Inventor	LAST NAME	FIRST NAME	MIDDLE NAME	Residence: CITY	STATE or COUNTRY
	Post Office Address					CITIZENSHIP

I further declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like as made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing therefrom.

SIGNATURE OF INVENTOR 1 <i>Anthony Maglica</i>	SIGNATURE OF INVENTOR 2
DATE 8-29-84	DATE
SIGNATURE OF INVENTOR 3	SIGNATURE OF INVENTOR 4
DATE	DATE

0085129-082799

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In Re Application of)	Group Art Unit: 342
ANTHONY MAGLICA)	Examiner: R. Cox
Serial No. 648,032)	
Filed: September 6, 1984)	
For: MINIATURE FLASHLIGHT)	

jc675 U.S. PTO
09/305129
08/27/99

REVOCATION OF POWER OF ATTORNEY
AND POWER OF ATTORNEY

HONORABLE COMMISSIONER OF
PATENTS AND TRADEMARKS
Washington, D.C. 20231

Gentlemen:

ANTHONY MAGLICA, applicant of U. S. Patent Application
Serial No. 648,032, filed September 6, 1984, entitled
"MINIATURE FLASHLIGHT", do hereby revoke the previous power
of attorney to ROBERT K. WALLOR (Reg. No. 26,595), whose
address is:

SPENSLEY HORN JUBAS & LUBITZ
(1880 Century Park East, Fifth Floor
Los Angeles, California 90067

Telephone: (213) 553-5050

and do hereby appoint the registered attorneys listed below
of the law firm of LYON & LYON, 611 West Sixth Street, Los
Angeles, California 90017, Registration No. 11,611, whose members
are all admitted to the Bar of the State of California, as
its attorneys of record with full power of substitution and
revocation to prosecute this application to register, to transact
all business in the Patent and Trademark Office in connection
therewith, and to receive the Certificate of Registration:


0935129 082799

Robert Douglas Lyon	Reg. No. 16,772
Roland N. Smoot	Reg. No. 18,718
Conrad R. Solum, Jr.	Reg. No. 20,467
James W. Geriak	Reg. No. 20,233
Robert M. Taylor, Jr.	Reg. No. 19,848
Samuel B. Stone	Reg. No. 19,297
Douglas E. Olson	Reg. No. 22,798
Robert E. Lyon	Reg. No. 24,171
James J. Short	Reg. No. 25,922
Robert C. Weiss	Reg. No. 24,939
William E. Thomson, Jr.	Reg. No. 20,719
Richard E. Lyon, Jr.	Reg. No. 26,300
John D. McConaghy	Reg. No. 26,773
William C. Steffin	Reg. No. 26,811
Coe A. Bloomberg	Reg. No. 26,605
J. Donald McCarthy	Reg. No. 25,119
John M. Benassi	Reg. No. 27,483
James H. Shalek	Reg. No. 29,749
Roy L. Anderson	Reg. No. 30,240
Charles Berman	Reg. No. 29,249

Please mail all correspondence to LYON & LYON, as noted above, and direct telephone calls to (213) 489-1600, Attention: Charles Berman.

I, the undersigned, declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

DATED this 31st day of October, 1985.


ANTHONY MAGLICA

00385129-082799

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant(s):)	Group Art Unit: 2901
)	
ANTHONY MAGLICA)	Examiner:
)	
Serial No.: To Be Assigned)	
)	
Filed: Herewith)	
)	
For: FLASHLIGHT)	

ASSOCIATE POWER OF ATTORNEY (37 CFR 1.34)

Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:


Please recognize the following as an associate attorney in this application:

David A. Randall, Esq., Reg. No. 37,217
LYON & LYON LLP
633 West Fifth Street, 47th Floor
Los Angeles, CA 90071

Respectfully submitted,

LYON & LYON LLP

Dated: August 27, 1999

By 
Robert C. Weiss
Registration No. 24,939
Attorneys for Applicant

LYON & LYON LLP
633 West Fifth Street, Suite 4700
Los Angeles, California 90071-2066
Tel. No. (213) 489-1600